

SensorProx

Readers

The SensorProx range of readers are practical and easy to install. All the readers are epoxy filled and weatherproof therefore suitable for indoor and outdoor applications.

Key Features

- Low Frequency
- Metal back plate for easy installation
- Non-drop bottom screw
- Backlit reader and keypad
- Touch sensitive number pad with LED feedback
- Red, Green & Blue LED feedback

LED Feedback

The Logo and keypad (SP-KPV only) is backlit blue for easy identification. The back light changes Green for access granted or Red for access denied. This makes the readers very user friendly.

Modern Design

New smooth sleek black design makes this reader ideal for installs where aesthetics are a priority.

Single Gang

The SP-KPV and SP-SG are designed for US single gang mounting and also UK single gang mounting.

Metal Backplate

Metal back plate allows the reader to be on metal surface without affecting the read range.

Interactive Keypad

Keypad is constant backlit blue. When key is pressed the key illuminates bright blue indicating confirmation of key press.



SensorProx

Readers



Technical Specification

Reader Specification

LED	Blue, Red, Green
Weatherproof	Fully Potted IP 65
Reading Technology	Proximity
Read Range	50mm
Frequency	125 KHz
Function	Read Only
Interface	Wiegand

Physical

SP-MINI	85(H) x 55(W) x 17(D)mm
SP-SG	116(H) x 85(W) x 21(D)mm
SP-KPV	116(H) x 85(W) x 21(D)mm
Case Material	Plastic
Case Colour	Black

Environmental

Operating Temperatures	-30°C to +70°C
------------------------	----------------

Electrical

Operating Voltage	10 - 15 vDC
Operating Current	150mA (Max)



Part Numbers

SP-MINI	SensorProx mini proximity reader
SP-SG	SensorProx single gang proximity reader
SP-KPV	SensorProx single gang prox and pin reader
SP-ISO	SensorProx Format ISO Cards.
SP-KEY-R/G/B	SensorProx Format Red, Green or Blue Keyfobs.

Other reader formats & cards are available, please ask a member of staff for Part Numbers



SP-MINI



SP-SG



SP-KPV